



24V DC stainless steel recessed wall luminaires

Location and symmetric light distribution

Recessed wall luminaires that can be used as location luminaires or floodlights. This family is designed for interior or exterior installation in walls and other vertical surfaces and is available in a variety of housing sizes and light outputs.

Luminaires require a remote 24V DC class 2 power supply suitable to operate the intended LED wattage, see page 405.


Stainless steel housing and trim · Clear or matte safety glass
Aluminum installation housing

LED Color temperatures: 2700K, 3000K, 3500K, 4000K

BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at www.bega-us.com

Luminaires are provided with #4 brushed stainless steel trims.

NRTL listed to North American standards · Suitable for wet locations
Protection class IP 68



Location luminaire

	LED	A	B	C	D
33 880*	0.2 W	1 1/2	2 1/2	4 3/4	4
33 881*	0.5 W	2	3 1/8	4 5/8	4
33 882*	2.1 W	3	3	6	4



Symmetric

	LED	A	B	C	D
33 830*	0.3 W	1 1/2	2 1/2	4 3/4	4
33 831*	1.1 W	2	3 1/8	4 5/8	4
33 832*	4.5 W	3	3	6	4

* Remote driver required

