



Recessed wall luminaires
Unshielded or asymmetric light

Recessed wall luminaires with unshielded or asymmetric light distribution. The asymmetric light distribution is ideal for the glare-free illumination of ground surfaces, building entrances, stairs and footpaths. The unshielded luminaires have a directing and guiding light effect. The illuminance level on the lit surface is lower, but the ambient brightness is greater with increased vertical illuminance.

Luminaire 33 200 requires a remote 24 V DC class 2 power supply suitable to operate the intended LED wattage, see page 405.

Die-cast aluminum housing with stainless steel faceplate
Safety glass with optical texture or white glass
Reflector made of pure anodized aluminum


LED Color temperatures: 2700 K, 3000 K, 3500 K, 4000 K

BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at www.bega-us.com


Further LED technical data including delivered lumens, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at www.bega-us.com

Luminaires are provided with #4 brushed stainless steel trims.

NRTL listed to North American standards · Suitable for wet locations
Protection class IP 65



Unshielded			
	LED	A	B
33 200*	2.1 W	3 1/8"	4"
33 308	2.1 W	5 7/8"	4 3/4"
33 309	4.0 W	8 1/4"	4 5/8"



Asymmetric			
	LED	A	B
33 020	4.2 W	5 7/8"	4 3/4"
33 021	8.4 W	8 1/4"	4 5/8"

*Remote driver required

