



Recessed wall luminaires
Asymmetric or asymmetric wide spread distribution

For decades, BEGA has set the standard for recessed wall luminaires worldwide. Newly redesigned with a refined look, broader range of delivered lumens, and contractor friendly enhancements for ease of installation and quality assurance, BEGA's unwavering commitment to quality above all permeates everything about this new approach to recessed wall luminaires.

Recessed wall luminaires with asymmetric or asymmetric wide spread light distribution. The asymmetric distribution provides light in a forward orientation and is suitable for lighting ground surfaces, building entrances, and stairways. The asymmetric wide spread light distribution is ideally suited for illuminating corridors and pathways. Separate installation housing allows for seamless coordination into construction and easy maintenance.

Die-cast aluminum housing and faceplate · Composite installation housing
Safety glass with optical texture

LED color temperatures: 2700 K, 3000 K, 3500 K, 4000 K

BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at www.bega-us.com

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.


NRTL listed to North American standards · Suitable for wet locations
Protection class IP 65




Asymmetric
light distribution



Asymmetric wide spread
light distribution



Asymmetric				
	LED	A	B	C
33 053	4.1 W	6 5⁄8	2 3⁄4	5
33 054	5.9 W	10 1⁄8	2 3⁄4	5
33 055	8.4 W	12 1⁄2	2 3⁄4	5
33 058	12.3 W	13	4 7⁄8	5 1⁄2
33 059	16.4 W	16 1⁄2	4 7⁄8	5 1⁄2
33 060	20.5 W	20 1⁄2	4 7⁄8	5 1⁄2



Asymmetric wide spread				
	LED	A	B	C
33 023	4.0 W	6 5⁄8	2 3⁄4	5
33 046	5.9 W	10 1⁄8	2 3⁄4	5
33 049	7.8 W	12 1⁄2	2 3⁄4	5
33 062	12.3 W	13	4 7⁄8	5 1⁄2
33 067	16.4 W	16 1⁄2	4 7⁄8	5 1⁄2
33 098	20.5 W	20 1⁄2	4 7⁄8	5 1⁄2

