



**Stainless steel recessed wall luminaires**  
shielded or unshielded

A series of recessed wall luminaires with unshielded or shielded light distribution. The shielded light distribution is ideal for the glare-free illumination of ground surfaces, building entrances, stairs and footpaths. The unshielded luminaires have a directing and guiding light effect. The illuminance level on the lit surface is lower, but the ambient brightness is greater with increased vertical illuminance.

Die-cast aluminum housing  
Stainless steel faceplate with or without integral louvers  
White safety glass or clear safety glass

LED color temperatures: 2700K, 3000K, 3500K, 4000K

BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at [www.bega-us.com](http://www.bega-us.com)

Luminaires are provided with #4 brushed stainless steel trims.


NRTL listed to North American standards · Suitable for wet locations  
Protection class IP 64




Recessed luminaire  
Unshielded light



Location luminaire  
Shielded light



Unshielded					
	LED	A	B	C	CPC
22 130	3.4 W	7 ½	3 ⅝	4	19 535
22 131	6.7 W	10 ⅞	3 ⅝	4	19 536
22 132	10.1 W	12 ¾	3 ⅝	4	19 601



Shielded					
	LED	A	B	C	CPC
22 135	3.4 W	7 ½	3 ⅝	4	19 535
22 136	6.7 W	10 ⅞	3 ⅝	4	19 536
22 137	10.1 W	12 ¾	3 ⅝	4	19 601

