

Recessed wall luminaires
Directed light

For decades, BEGA has set the standard for recessed wall luminaires worldwide. Newly redesigned with a refined look, broader range of delivered lumens, and contractor friendly enhancements for ease of installation and quality assurance, BEGA's unwavering commitment to quality above all permeates everything about this new approach to recessed wall luminaires.

Recessed wall luminaires with asymmetric flat beam light distribution. These luminaires are particularly suitable for lighting ground level surfaces, corridors and pathways. A separate installation housing allows for seamless coordination into various construction types and easy maintenance.

Die-cast aluminum housing with die-cast aluminum faceplate
Composite installation housing · Safety glass with optical texture
Reflector made of pure anodized aluminum

LED color temperatures: 2700 K, 3000 K, 3500 K, 4000 K



BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at www.bega-us.com.

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.

NRTL listed to North American standards · Suitable for wet locations
Protection class IP 65



Recessed luminaire
Directed light



Directed light			
	LED	A	B
24 110	6.0 W	5 1/8"	5 1/2"
24 111	8.9 W	7 3/8"	5 1/2"
24 112	16.3 W	9 7/8"	5 1/2"

