



**Impact-resistant luminaires**

Unshielded or shielded

A series of impact-resistant wall mounted luminaires made of die-cast aluminum and crystal glass. The exceptional material thickness and strength of crystal glass provides this luminaire group with robustness and defines their character. Arranged individually or in groups, they are great design elements for a host of lighting applications.

Die-cast aluminum · Crystal glass with optical texture

LED color temperatures: 2700K, 3000K, 3500K, 4000K

BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at [www.bega-us.com](http://www.bega-us.com)

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.

NRTL listed to North American standards · Suitable for wet locations  
Protection class IP 65



Ceiling and wall luminaires · **Unshielded**

	LED	A	B	C
<b>24 598</b> ADA	3.9 W	8 3/8"	4 1/4"	3 7/8"
<b>24 599</b>	7.9 W	11 1/8"	6 1/8"	4 7/8"



Wall luminaires · **Shielded**

	LED	A	B	C
<b>22 649</b>	3.8 W	8 3/8"	4 3/4"	4 1/4"
<b>22 656</b>	7.9 W	11 1/8"	6 1/8"	5 3/8"