




One-sided



Two-sided

Wall luminaires
with light emission on one or two sides

A series of wall luminaires with light output in one or two directions. Ideal for upward and downward lighting effects for interior and exterior locations. Arranged individually or in groups, they are great design elements for a host of lighting applications.

BEGA 19 545 and 19 537 small opening wiring box (included) required for proper installation.


Die-cast aluminum · White safety glass

LED color temperatures: 2700 K, 3000 K, 3500 K, 4000 K

BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at www.bega-us.com

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure[®] finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.

NRTL listed to North American standards · Suitable for wet locations
Protection class IP 64



Light emission on one side					
	LED	A	B	C	Required wiring box
33 319	3.9 W	7 7⁄8	2 1⁄8	4 3⁄4	19 545
33 329	7.9 W	11 7⁄8	2 1⁄8	4 3⁄4	19 537

Light emission on two sides					
	LED	A	B	C	Required wiring box
33 340	3.9 W	7 7⁄8	2 1⁄8	4 3⁄4	19 545
33 341	7.9 W	11 3⁄4	2 1⁄8	4 3⁄4	19 537