

**Wall luminaires**  
with directed light

A series of wall mounted luminaires with directed light. These luminaires can be mounted at various heights for general purpose illumination or specific task illuminance when mounted below eye level.


Die-cast aluminum · Matte safety glass

LED color temperatures: 2700K, 3000K, 3500K, 4000K

BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at [www.bega-us.com](http://www.bega-us.com)

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.

NRTL listed to North American standards · Suitable for wet locations  
Protection class IP 65



Wall luminaires					
		LED	A	B	C
24 372	ADA	3.1 W	8 ½	4 ¾	3 ¼
24 374	ADA	12.3 W	12 ¾	4 ¾	3 ¾
24 373	ADA	18.4 W	16 ¾	4 ¾	3 ¾