

Wall luminaires
with light emission on one or two sides

A series of wall mounted luminaires with light emission in one or two directions. Arranged individually or in groups, they are great design elements for a host of lighting applications.


Die-cast aluminum · Matte safety glass

LED color temperatures: 2700 K, 3000 K, 3500 K, 4000 K

BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at www.bega-us.com

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.

NRTL listed to North American standards · Suitable for wet locations
Protection class IP 65



Light emission on one side				
		LED	A	B C
22 359	ADA	7.7 W	8 ½	4 ¾ 4
22 360	ADA	15.4 W	12 ½	4 ¾ 4
Light emission on two side				
		LED	A	B C
22 363	ADA	7.7 W	8 ½	4 ¾ 4
22 365	ADA	15.4 W	12 ½	4 ¾ 4