



Wall luminaires
with directed light

A series of wall mounted luminaires with symmetric or asymmetrical light distribution. This group of luminaires is designed for general illumination of pathways, walkways and plazas.

Luminaire 22 228 requires a remote 24 V DC class 2 power supply suitable to operate the intended LED wattage, see page 405.

Die-cast aluminum · White safety glass
Reflector made of pure anodized aluminum

LED color temperatures: 2700 K, 3000 K, 3500 K, 4000 K

BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at www.bega-us.com

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.

NRTL listed to North American standards · Suitable for wet locations
Protection class IP 65



Wall luminaires				
		LED	A	B C
22 228*	ADA	2.9 W	4 3/4	4 3/4 2 5/8
22 292	ADA	7.9 W	6 3/8	6 3/8 3 3/4
22 256		17.8 W	8	8 7 7/8
22 260		29.8 W	11 1/8	11 1/8 8

* Remote driver required