

Wall luminaires
with light emission on one or two sides

A series of wall mounted luminaires with light emission on one or two sides. Downward directed light distribution is ideal for general illumination of pathways and corridors. Luminaires provided with upward directed light available in narrow or very narrow distributions and are ideal for highlighting various architectural features.


Die-cast aluminum · Safety glass
Reflector made of pure anodized aluminum

LED color temperatures: 2700 K, 3000 K, 3500 K, 4000 K

BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at www.bega-us.com

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.

NRTL listed to North American standards · Suitable for wet locations
Protection class IP 64



Narrow beam downward						
		LED	β	A	B	C
	33 579	ADA 1.9 W	20°	3	5 1⁄8	3 3⁄4
	33 580	4.0 W	20°	4 3⁄8	7 1⁄2	5
	33 581	7.9 W	25°	5 1⁄8	9	6
	24 582	16.5 W	16°	5 7⁄8	10 5⁄8	6 7⁄8

Narrow beam upward · Narrow beam downward						
		LED	β	A	B	C
	33 590	ADA 3.8 W	20°	3	5 1⁄8	3 3⁄4
	33 591	8.0 W	20°	4 3⁄8	7 1⁄2	5
	33 592	15.8 W	25°	5 1⁄8	9	6
	24 593	33.0 W	16°	5 7⁄8	10 5⁄8	6 7⁄8

Very narrow beam upward · Narrow downward						
		LED	β	A	B	C
	24 594	ADA 3.8 W	13/20°	3	5 1⁄8	3 3⁄4
	24 595	8.0 W	12/17°	4 3⁄8	7 1⁄2	5
	24 596	15.8 W	9/20°	5 1⁄8	9	6
	24 597	33.0 W	9/20°	5 7⁄8	10 5⁄8	6 7⁄8

β = Beam angle