



Ceiling and wall luminaires  
Unshielded

This series of ceiling and wall luminaires offer new design opportunities with linear lighting elements. Their light accentuates the linear structures of buildings. Available in lengths that go far beyond traditional luminaires, these luminaires distribute their unshielded light in three directions, offering quality illumination with maximum visual comfort. The white synthetic diffuser distributes the light gently and evenly. Individually, in groups or as bands of light, the new linear ceiling and wall luminaires form effective design elements. As wall luminaires, they can be installed horizontally or vertically.

Die-cast aluminum · White acrylic diffuser

LED color temperatures: 2700 K, 3000 K, 3500 K, 4000 K

BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at [www.bega-us.com](http://www.bega-us.com)

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.

NRTL listed to North American standards · Suitable for wet locations  
Protection class IP 65



Ceiling and wall luminaires				
	LED	A	B	C
<b>24 115</b>	11.1 W	19 ¾"	4 7⁄8"	4 5⁄8"
<b>24 116</b>	22.4 W	37 ¼"	4 7⁄8"	4 5⁄8"
<b>24 117</b>	44.4 W	72 ¼"	4 7⁄8"	4 5⁄8"

