

**Downlights  
with adjustable light distribution**

Electronic driver location	ceiling pan
Delivered lumens	360 · 1695 lm
Luminaire size	Ø 4 1/2 · 5 7/8 · 8 7/8 · 10 3/8
Glass	safety glass

**Downlights  
with adjustable light distribution**

A series of downlights with adjustable light distribution. The inclination angle of the luminaires is infinitely adjustable from 0° to 30°. The optical assembly can be rotated 360° around the vertical axis. The adjustable optical system makes these luminaires ideal for solving a myriad of lighting tasks. This family of luminaires is also available with RGBW for additive color mixing or Tunable White technology.


Die-cast aluminum housing, optical assembly and trim ring · Clear safety glass  
Reflector surface made of pure anodized aluminum







LED color temperatures: 2700K, 3000K, 3500K, 4000K

BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at [www.bega-us.com](http://www.bega-us.com)

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.

NRTL listed to North American standards · Suitable for wet locations  
Protection class IP 65



Adjustable · Static white								
	LED	β	A	B	C			
55 841	3.0 W	33°	4 1/2	4 1/2	18	10 042	10 013	
55 842	5.7 W	16°	5 7/8	4 1/2	18	10 043	10 014	
24 047	11.5 W	13°	8 7/8	5	18	10 047	10 016	
55 844	18.0 W	13°	10 3/8	5	20	10 048	10 019	
Adjustable · RGBW								
	LED	β	A	B	C			
24 837	16.7 W	17°	8 7/8	5	18	10 047	10 016	
24 838	23.4 W	15°	10 3/8	5	20	10 048	10 019	
Adjustable · Tunable white								
	LED	β	A	B	C			
24 835	9.7 W	22°	8 7/8	5	18	10 047	10 016	
24 836	11.5 W	21°	10 3/8	5	20	10 048	10 019	

β = Beam angle

