



Surface-mounted downlights

Symmetric light distribution

A series of compact ceiling mounted downlights with partially frosted crystal glass. Designed for lighting atriums, canopies, passages, and a variety of other interior and exterior locations, the partially frosted crystal glass creates an additional vertical light component that supplements the downlight.

Luminaires in this series require a remote 24 V DC class 2 power supply suitable to operate the intended LED wattage, see page 405.

Die-cast aluminum · Partially frosted crystal glass
Reflector made of pure anodized aluminum.

LED color temperatures: 2700 K, 3000 K, 3500 K, 4000 K

BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at www.bega-us.com

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.

NRTL listed to North American standards · Suitable for wet locations
Protection class IP 65



Surface mounted downlights					
	LED	β	A	B	Required wiring box
66 055	3.0 W	71°	3 3/4"	3 3/8"	19 538
66 050*	4.9 W	69°	3 3/4"	3 3/8"	19 538
66 056	4.9 W	65°	4 7/8"	4 5/8"	—
66 051	10.0 W	57°	5 7/8"	5 1/4"	—
66 057	15.7 W	53°	7 1/2"	6 3/8"	—
66 058	35.7 W	46°	8 5/8"	6 3/4"	—

β = Beam angle
*Remote driver required