



Ground mounted luminaires

A series of walk over luminaires to illuminate ground surfaces. Equipped with two or four light apertures to meet different lighting requirements. These luminaires affix to a recessed BEGA junction box, supplied with luminaire, eliminating the need for deep recessed housings.

Luminaires 77 069 and 77 070 require a remote 24 V DC class 2 power supply suitable to operate the intended LED wattage, see page 405.

Die-cast aluminum · Clear safety glass  
Reflector made of pure anodized aluminum

LED color temperatures: 2700K, 3000K, 3500K, 4000K

BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at [www.bega-us.com](http://www.bega-us.com)

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.

NRTL listed to North American standards · Suitable for wet locations  
Protection class IP 67



Twin 90° ports				
	LED	A	B	C
77 069*	1.1 W	6 1/4	1 1/2	1 3/4
77 089	5.9 W	10 1/2	2 1/4	1 1/2



Four 60° ports				
	LED	A	B	C
77 070*	2.2 W	6 1/4	1 1/2	1 3/4
77 090	11.8 W	10 1/2	2 1/4	1 1/2

\* Remote driver required

Ground mounted luminaires

Pressure loads	2200 lbs.
Material	Die-cast aluminum
Protection class	IP 67
Installation depth	1 1/2 · 1 3/4 inch
Diameter Ø	6 1/4 · 10 1/2 inch

