



In-grade floodlights
Wall washer

The design of these in-grade floodlights makes it possible to fully illuminate a vertical surface, from the ground up to the edge of the roof. The lower limit of the light distribution is a straight line, without the usual “scallop”. The luminaires are mounted in a recessed housing on a foundation that absorbs the pressure loads. The luminaires can be driven over by vehicles with pneumatic tires. The luminaires must not be used in areas where they are exposed to horizontal loads caused by braking, accelerating and changes of direction.

Die-cast aluminum with cast-bronze cover · Installation housing made of stainless steel
Hardened crystal class · Silicone diffusing lens · Reflector made of pure anodized aluminum

LED color temperatures: 2700K, 3000K, 3500K, 4000K

BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at www.bega-us.com

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.

Luminaire 84 175 is provided with a natural cast bronze cover. Time and weather factors will create the natural patina of bronze.

NRTL listed to North American standards · Suitable for wet locations · Protection class IP 67



Wall washer					
	LED	A	B	C	D
84 618	24.6 W	11 ¼	13 ⅝	4 ⅜	2 ⅜
Wall washer · Bronze					
	LED	A	B	C	D
84 175	24.6 W	11 ¼	13 ⅝	4 ⅜	2 ⅜

