



**In-grade luminaires**  
Small scale

A series of in-grade location luminaires and floodlights for flush-mounted installations. Designed for directional or indicator lighting, uplighting of trees, walls, columns, or signage from ground surfaces.

Luminaires require a remote 24V DC class 2 power supply suitable to operate the intended LED wattage, see page 405.

Stainless steel housing and faceplate · White or clear safety glass  
Reflectors made of pure anodized aluminum

LED color temperatures: 2700 K, 3000 K, 3500 K, 4000 K

BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at [www.bega-us.com](http://www.bega-us.com)

Luminaires are provided with #4 brushed stainless steel trims.

NRTL listed to North American standards · Suitable for wet locations  
Protection class IP 68



Location luminaire				
square	LED	A	B	C
77 127*	0.6 W	3	1 5⁄8	2 3⁄8
77 128*	2.1 W	4 5⁄8	3 1⁄8	3 7⁄8



Symmetric					
square	LED	β	A	B	C
77117*	1.2 W	38°	3	1 5⁄8	2 3⁄8
77118*	3.0 W	33°	4 5⁄8	3 1⁄8	3 7⁄8



Asymmetric					
square	LED	β	A	B	C
77119*	3.0 W	34°/35°	4 5⁄8	3 1⁄8	3 7⁄8



Location luminaire				
round	LED	A	B	C
77 027*	0.6 W	3	1 5⁄8	2 3⁄8
77 028*	2.1 W	4 1⁄2	3	3 7⁄8



Symmetric					
round	LED	β	A	B	C
77 017*	1.2 W	38°	3	1 5⁄8	2 3⁄8
77 018*	3.0 W	33°	4 1⁄2	3	3 7⁄8



Asymmetric					
round	LED	β	A	B	C
77 019*	3.0 W	34°/35°	4 1⁄2	3	3 7⁄8

β = Beam angle      \* Remote driver required

