



In-grade luminaires

Square in-grade location luminaires and asymmetric floodlights. These luminaires are designed to bear pressure loads up to 11,000 lbs. from vehicles with pneumatic tires. The luminaires must not be used for traffic lanes where they are subject to horizontal pressure from vehicles braking, accelerating and changing direction.

Die-cast aluminum housing · Stainless steel faceplate · White or clear safety glass

LED color temperatures: 2700 K, 3000 K, 3500 K, 4000 K

BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at www.bega-us.com

Luminaires are provided with #4 brushed stainless steel trims.

NRTL listed to North American standards · Suitable for wet locations
Protection class IP 67



Location luminaires · white safety glass				
	LED	A	B	C
77 050	3.7 W	6 ¼	6	3 ¾
77 051	4.0 W	10	9 ⅝	4 ⅝
77 052	10.5 W	13	12 ⅙	6 ¼
77 053	15.7 W	17 ⅜	16 ½	6 ¼



Asymmetric floodlights · clear safety glass					
	LED	β	A	B	C
77 023	7.8 W	67 × 105°	6 ¼	6	3¾
77 024	17.9 W	59 × 100°	10	9⅝	4⅞

β = Beam angle

