



Compact floodlights
with mounting canopy

A series of very compact floodlights with mounting canopy.
This family of floodlights is available in various sizes and light distributions. When paired
with the comprehensive range of accessories, this family of luminaires sets the floodlighting
standard with regards to cost effectiveness, compactness and efficiency.

Luminaires 77 604 and 77 607 require a remote 24V DC class 2 power supply suitable
to operate the intended LED wattage, see page 405.

Die-cast aluminum · Safety glass · Reflector made of pure anodized aluminum

LED color temperatures: 2700K, 3000K, 3500K, 4000K

BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement
modules guaranteed for up to 20 years after date of purchase. Further LED technical data
including luminous flux, CRI, dimming and electrical characteristics are provided on the
individual luminaire specification sheets, available at www.bega-us.com

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness.
BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in
Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and
custom colors, are a polyester powder.

NRTL listed to North American standards · Suitable for wet locations · Protection class IP 65

Accessories:



360° glare shield




180° glare shield



Louver



Elliptical spread
lens



84 362
98 016

Compact floodlight · very narrow								Accessories		
	LED	β	A	B	C	D	Required wiring box			
77 680	9.0 W	8°	5 5/8	8 1/8	6	4	—	70 075	70 756	70 712
77 700	12.5 W	9°	6 1/4	8 3/4	6 1/2	4	—	70 076	70 757	70 720
77 639	47.5 W	10°	9 1/8	12	8 3/4	5 1/8	—	70 077	70 758	70 721
77 709	73.5 W	17°	9 1/8	12	8 3/4	5 1/8	—	70 077	70 758	70 721

Compact floodlight · narrow								Accessories		
	LED	β	A	B	C	D	Required wiring box			
77 604*	7.9 W	28°	4 1/8	6	4 1/4	3 5/8	19 538	70 050	70 755	—
77 681	8.9 W	33°	5 5/8	8 1/8	5 5/8	4	—	70 055	70 756	70 760
77 701	19.2 W	26°	6 1/4	8 3/4	6 1/2	4	—	70 060	70 757	70 796
77 659	47.5 W	25°	9 1/8	12	8 3/4	5 1/8	—	70 065	70 758	70 775
77 739	73.5 W	21°	9 1/8	12	9	5 1/8	—	70 065	70 758	70 775

Compact floodlight · wide								Accessories		
	LED	β	A	B	C	D	Required wiring box			
77 607*	7.9 W	47°	4 1/8	6	4 1/4	3 5/8	19 538	70 050	70 755	—
77 682	12.9 W	46°	5 5/8	8 1/8	5 5/8	4	—	70 055	70 756	—
77 702	19.2 W	44°	6 1/4	8 3/4	6 1/2	4	—	70 060	70 757	—
77 689	47.5 W	51°	9 1/8	12	8 3/4	5 1/8	—	70 065	70 758	—
77 749	73.5 W	51°	9 1/8	12	9	5 1/8	—	70 065	70 758	—

Compact floodlight · narrow · RGB W								Accessories		
	LED	β	A	B	C	D	Required wiring box			
98 016	39.0 W	25°	9 1/8	13 7/8	8 7/8	9 3/8	—	70 065	70 758	—

Compact floodlight · wide · RGB W								Accessories		
	LED	β	A	B	C	D	Required wiring box			
84 362	39.0 W	48°	9 1/8	13 7/8	8 7/8	9 3/8	—	70 065	70 758	—



Elliptical spread lens



Louver



180° glare shield



360° glare shield

β = Beam angle

* Remote driver required

Page 170



1/2" I.P.S. nipple

Page 172



Outrigger arm

