



Performance floodlights
with mounting canopy

A series of compact performance floodlights with mounting canopy. This family of floodlights is available in very narrow, narrow, and wide beam distributions. When paired with the comprehensive range of accessories, this family of luminaires sets the floodlighting standard with regards to cost effectiveness, compactness and efficiency.

Die-cast aluminum · Safety glass · Silicone optics · Reflector surface made of pure aluminum
BEGA Hybrid Optics®

LED color temperatures: 2700K, 3000K, 3500K, 4000K

BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at www.bega-us.com

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.


NRTL listed to North American standards · Suitable for wet locations · Protection class IP 65









With louver









With 180° shield



	Performance floodlight · very narrow						Accessories		
	LED	β	A	B	C	D			
84 504	38.1 W	11°	6 7/8	8 7/8	4	4	71 113	71 111	—
84 544	72.9 W	11°	9 7/8	12 1/4	5 1/8	5 1/8	71 074	71 072	—

	Performance floodlight · narrow						Accessories		
	LED	β	A	B	C	D			
84 505	37.5 W	21°	6 7/8	10	4	4	71 113	71 111	71 112
84 545	71.1 W	28°	9 7/8	13 7/8	5 1/2	5 1/8	71 074	71 072	71 073

	Performance floodlight · wide						Accessories		
	LED	β	A	B	C	D			
84 506	37.5 W	63°	6 7/8	10	4	4	71 113	71 111	—
84 546	71.1 W	57°	9 7/8	13 7/8	5 1/2	5 1/8	71 074	71 072	71 073

 Elliptical spread lens  180° glare shield  Louver β = Beam angle



1/2" I.P.S. nipple