



Performance floodlights  
with ½" I.P.S. nipple

A series of compact performance floodlights with ½" I.P.S. nipple for direct attachment to cast boxes or other accessories. This family of floodlights is available in very narrow, narrow, and wide beam distributions. When paired with the comprehensive range of accessories, this family of luminaires sets the floodlighting standard with regards to cost effectiveness, compactness and efficiency.

Die-cast aluminum · Safety glass · Silicone optics · Reflector surface made of pure aluminum  
BEGA Hybrid Optics®

LED color temperatures: 2700K, 3000K, 3500K, 4000K

BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at [www.bega-us.com](http://www.bega-us.com)

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.


NRTL listed to North American standards · Suitable for wet locations · Protection class IP 65









With louver









With 180° shield



	Performance floodlight · <b>very narrow</b>					Accessories		
	LED	β	A	B	C			
<b>84 526</b>	38.1 W	10°	6 7/8	10	4	<b>71 113</b>	<b>71 111</b>	—
<b>84 547</b>	72.9 W	11°	9 7/8	13 3/4	5 1/8	<b>71 074</b>	<b>71 072</b>	—

	Performance floodlight · <b>narrow</b>					Accessories		
	LED	β	A	B	C			
<b>84 527</b>	37.5 W	21°	6 7/8	10	4	<b>71 113</b>	<b>71 111</b>	<b>71 112</b>
<b>84 548</b>	71.1 W	28°	9 7/8	13 7/8	5 1/2	<b>71 074</b>	<b>71 072</b>	<b>71 073</b>

	Performance floodlight · <b>wide beam</b>					Accessories		
	LED	β	A	B	C			
<b>84 528</b>	37.5 W	63°	6 7/8	10	4	<b>71 113</b>	<b>71 111</b>	—
<b>84 549</b>	71.1 W	57°	9 7/8	13 7/8	5 1/2	<b>71 074</b>	<b>71 072</b>	<b>71 073</b>

 Elliptical spread lens     180° glare shield     Louver    β = Beam angle



½" I.P.S. nipple  
accessories 19 593  
(surface mounted conduit  
wiring box) and 19 594  
(direct burial wiring box)  
available.



Mounting canopy

