



High-performance floodlights
with mounting yoke

A series of large-scale rectangular high-output floodlights with mounting yoke. This family of floodlights is available in wide and flat beam distributions. Designed for lighting applications where a very high light output is required such as bridges, large signage and building facades.




Die-cast aluminum · Safety glass · Reflector made of pure anodized aluminum



LED color temperatures: 2200 K, 2700 K, 3000 K, 3500 K, 4000 K



BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at www.bega-us.com

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.

NRTL listed to North American standards · Suitable for wet locations
Protection class IP 67



	Floodlights · wide					Accessories	
	LED	β	A	B	C		
84 500	174.0 W	70/62°	18 5⁄8	19 1⁄2	3 3⁄8	71 107	71 108
84 501	347.0 W	77/59°	22 1⁄4	26 3⁄8	3 3⁄8	71 104	71 102

	Floodlights · flat beam					Accessories	
	LED	β	A	B	C		
84 502	174.0 W	26/72°	18 5⁄8	19 1⁄2	3 3⁄8	71 106	71 108
84 503	347.0 W	27/77°	22 1⁄4	26 3⁄8	3 3⁄8	71 103	71 102

