



Surface washer floodlights

with mounting canopy, ½" I.P.S. nipple or outrigger arm

Surface washer floodlights with asymmetric wide beam light distribution. Compact, powerful and versatile in three installation types.


Die-cast aluminum · Safety glass · Reflector made of pure anodized aluminum

LED color temperatures: 2700 K, 3000 K, 3500 K, 4000 K


BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at www.bega-us.com

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.


NRTL listed to North American standards · Suitable for wet locations
Protection class IP 65



Floodlights with mounting canopy						
	LED	β	A	B	C	D
84 098	19.4 W	72°	10 ¼	4 ⅛	14 ⅞	4 ½



Floodlights with ½" I.P.S. nipple						
	LED	β	A	B	C	D
84 099	19.4 W	72°	10 ¼	4 ⅛	13 ⅞	—



Floodlights with outrigger arm						
	LED	β	A	B	C	D
84 100	19.4 W	72°	10 ¼	4 ⅛	28 ⅞	7 ½

β = Beam angle


Page 400



½" I.P.S. nipple accessories 19 593 (surface mounted conduit wiring box) and 19 594 (direct burial wiring box) available.



½" I.P.S. nipple



Outrigger arm

