

**Garden bollards**  
with shielded wide beam light distribution

A series of pathway luminaires with shielded wide beam light distribution for use in the private sector. These luminaires are ideally suited for gardens, entryways, and for many applications on paths and terraces. Anchorage units are available for direct burial in concrete or soil, or with a hardscape base for installation on foundations or paved surfaces.


Die cast and extruded aluminum · Clear safety glass  
Galvanized steel anchorage

LED color temperatures: 2700 K, 3000 K, 3500 K, 4000 K

BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at [www.bega-us.com](http://www.bega-us.com)

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.

NRTL listed to North American standards · Suitable for wet locations  
Protection class IP 65



Garden bollards		LED	A	B	C
<b>77 276</b>	with direct burial anchorage	2.1 W	2 7/8	10	3 1/2
<b>77 277</b>	with hardscape base	2.1 W	2 7/8	10	3 1/2

