



Symmetric



Asymmetric

Garden floodlight
with earth spike

A very compact floodlight with earth spike and adjustable knuckle. This luminaire is ideally suited for highlighting architecture and landscape elements around the home and garden. The earth spike mounting allows for easy relocation as a landscape evolves.


Die-cast aluminum · Reinforced polyamide · Clear safety glass
Reflector made of pure anodized aluminum

LED color temperatures: 2700 K, 3000 K, 3500 K, 4000 K

BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at www.bega-us.com

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection. Luminaire provided in standard BEGA Black, custom colors not available.

NRTL listed to North American standards · Suitable for wet locations
Protection class IP 65



Floodlight with earth spike					
	LED	β	A	B	C
84 067	3.0 W	32°	4 1⁄8	15 3⁄8	4 7⁄8

β = Beam angle



Garden in-grade

with symmetric or asymmetric light distribution

A series of in-grade floodlights with symmetric or asymmetric light distribution. This family of luminaires is resistant to foot traffic and is ideally suited for the illumination of architectural details for landscape features around the home and garden.


Reinforced polyamide · Clear safety glass
Reflector made of pure anodized aluminum

LED color temperatures: 2700 K, 3000 K, 3500 K, 4000 K

BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at www.bega-us.com

Luminaires are provided with #4 brushed stainless steel trims.

NRTL listed to North American standards · Suitable for wet locations
Protection class IP 65



Floodlight · symmetric				
	LED	A	B	C
77 010	3.0 W	4 3⁄8	2 3⁄4	4 7⁄8

Floodlight · asymmetric				
	LED	A	B	C
77 008	3.0 W	4 3⁄8	2 3⁄4	4 7⁄8

