



Bollards

with unshielded, wide spread or shielded light

A series of bollard luminaires with unshielded, wide spread or shielded light distribution. Unshielded bollards provide brilliant illumination of ground surfaces as well as a high level of vertical illuminance perfect for illuminating people or architectural elements. The wide spread light distribution is perfect for the illumination of walkways and paths. Bollards with shielded light distribution are ideal for providing a high level of illuminance directly in front of the luminaires while providing exceptional glare control.


Die-cast and extruded aluminum · White, optically textured or clear safety glass · Reflector made of pure anodized aluminum

LED color temperatures: 2700K, 3000K, 3500K, 4000K

BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at www.bega-us.com

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.

NRTL listed to North American standards · Suitable for wet locations
Protection class IP 65



Bollards with unshielded light

	LED	A	B	C	Anchorage
84 669	12.6 W	13 1/4	15 3/4	3 7/8	79 825
84 670	12.6 W	13 1/4	31 1/2	3 7/8	79 825

Bollards with wide spread light distribution

	LED	A	B	C	Anchorage
84 673	12.6 W	13 1/4	15 3/4	3 7/8	79 825
84 674	12.6 W	13 1/4	31 1/2	3 7/8	79 825

Bollards with shielded light

	LED	A	B	C	Anchorage
84 671	12.3 W	13 1/4	15 3/4	3 7/8	79 825
84 672	12.3 W	13 1/4	31 1/2	3 7/8	79 825



Unshielded light

Wide spread light distribution

Shielded light



Unshielded light

Wide spread light distribution

Shielded light