



Unshielded bollards
with safety guard

A series of bollard luminaires with unshielded, symmetric light distribution. The light is uniformly distributed by a white, impact resistant acrylic diffuser. These robust luminaires can delineate and structure outside areas. Provided with mounting system that allows the luminaire to be adjusted independent of anchor bolt orientation.

Die-cast and extruded aluminum · White acrylic diffuser

LED color temperatures: 2700K, 3000K, 3500K, 4000K

BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at www.bega-us.com

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.

NRTL listed to North American standards · Suitable for wet locations
Protection class IP 65



Light building elements, Page 322



Unshielded bollard				
	LED	A	B	Anchorage
84 666	7.6 W	4¾	31½	79 824
84 667	22.8 W	6¼	43⅞	79 817
84 668	32.0 W	8⅝	47⅞	79 818

