



**Unshielded bollards**  
with safety guard

A series of bollard luminaires with unshielded symmetric light distribution. The light is uniformly distributed by a white, impact resistant acrylic diffuser. These robust luminaires can delineate and structure outside areas. Provided with mounting system that allows the luminaire to be adjusted independent of anchor bolt orientation.

Die-cast and extruded aluminum · White acrylic diffuser

LED color temperatures: 2700 K, 3000 K, 3500 K, 4000 K

BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at [www.bega-us.com](http://www.bega-us.com)

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.

NRTL listed to North American standards · Suitable for wet locations  
Protection class IP 65



Unshielded bollards				
	LED	A	B	Anchorage
<b>84 602</b>	15.6 W	6 ¼	33 ½	<b>79 817</b>
<b>84 603</b>	31.2 W	9	42	<b>79 818</b>

