



Bollards
with directed light

A series of bollard luminaires with indirect light distribution. The light is directed onto the top reflector and then redirected downward onto the illuminated surface. These luminaires are ideal where glare-free illumination is required. Provided with mounting system that allows the luminaire to be adjusted independent of anchor bolt orientation.

Die-cast and extruded aluminum · Clear safety glass
Reflector made of pure anodized aluminum

LED color temperatures: 2700 K, 3000 K, 3500 K, 4000 K

BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at www.bega-us.com

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.

NRTL listed to North American standards · Suitable for wet locations
Protection class IP 65



Bollards					Anchorage
	LED	A	B	C	
77 586	19.2 W	10 ¼	23 ¾	5 ½	79 817
77 589	19.2 W	10 ¼	31 ⅝	5 ½	79 817
84 610	36.3 W	12	43 ⅞	6 ½	79 817

