

**Bollards**  
with directed light

A series of bollard luminaires with wide spread or asymmetric light distribution. The wide spread light distribution is perfect for the illumination of walkways and paths. Bollards with shielded light are ideal for providing a high level of illuminance directly in front of the luminaires while providing exceptional glare control. Provided with mounting system that allows the luminaire to be adjusted independent of anchor bolt orientation.


Die-cast and extruded aluminum · Optically textured or clear safety glass  
Reflector made of pure anodized aluminum

LED color temperatures: 2700K, 3000K, 3500K, 4000K

BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at [www.bega-us.com](http://www.bega-us.com)

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.

NRTL listed to North American standards · Suitable for wet locations  
Protection class IP 65



Asymmetric light distribution					
	LED	A	B	C	Anchorage
<b>99 554</b>	3.9 W	6 ¼	31 ½	4 ¾	<b>79 824</b>
<b>99 558</b>	11.8 W	9 ¾	43 ¼	5 ½	<b>79 817</b>

Wide spread light distribution					
	LED	A	B	C	Anchorage
<b>99 552</b>	5.8 W	6 ¼	31 ½	4 ¾	<b>79 824</b>
<b>99 560</b>	17.9 W	9 ¾	43 ¼	5 ½	<b>79 817</b>



Asymmetric

Wide spread