



Page 272



Page 106

Light building element with unshielded light

A series of light building elements with unshielded light distribution. Light building elements are luminous design features for public areas. They are ideally suited for delineating and structuring interior and exterior spaces such as landscape areas, plazas, building entrances and atria.

Die-cast and extruded aluminum · White acrylic diffuser
Anchorage unit made of galvanized steel

LED color temperatures: 2700 K, 3000 K, 3500 K, 4000 K

BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at www.bega-us.com

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.

NRTL listed to North American standards · Suitable for wet locations · Protection class IP 65



| Light building elements | | | | | Anchorage |
|-------------------------|--------|------|------|-------|---------------|
| | LED | A | B | C | |
| 84 875 | 45.6 W | 6 ¼ | 48 ⅞ | 157 ½ | 79 803 |
| 84 876 | 55.2 W | 8 ⅞ | 52 ⅞ | 196 ⅞ | 79 801 |
| 99 877 | 86.4 W | 15 ¾ | 52 | 200 ¾ | 79 813 |

