



Concealed antenna and router housing

WiFi enabled light building elements
Symmetric or asymmetric wide beam light distribution

Designed for public spaces to provide illumination and internet from a single source, the WiFi hardware of your choice may be easily integrated into this BEGA luminaire.


Die-cast and extruded aluminum · Clear acrylic diffuser
Reflector made of pure anodized aluminum · Four integral dual-band antennas

LED color temperatures: 2700 K, 3000 K, 3500 K, 4000 K


BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at www.bega-us.com

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.


NRTL listed to North American standards · Suitable for wet locations
Protection class IP 65



Symmetric



Asymmetric wide beam



Symmetric		Asymmetric wide beam					
	LED	LED	A	B	C	D	
84 122	46.8 W	84 128	46.8 W	8 ½°	27 ¾°	196 7/8°	39 ¾°
Symmetric · 1 floodlight		Asymmetric wide beam · 1 floodlight					
	LED	LED	β	A	B	C	D
84 129	46.8 W	84 130	46.8 W	—	8 ½°	27 ¾°	196 7/8°
	11.5 W		11.5 W	14°			39 ¾°



10047 10016

Spread lenses  wide beam  flat beam β = Beam angle

