



Area/roadway luminaires
with asymmetric wide beam light distribution

A series of area/roadway luminaires with asymmetric wide beam light distribution. These luminaires are available in single head, twin head and davit arm mountings. This family of luminaires is designed specifically to illuminate streets, squares, access roads and pedestrian zones with maximum glare control and minimal spill light.


- Die-cast aluminum
- Clear safety glass with anti-reflective coating for increased transmission
- Reflector made of pure anodized aluminum

LED color temperatures: 2700 K, 3000 K, 3500 K, 4000 K


BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at www.bega-us.com

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.

NRTL listed to North American standards · Suitable for wet locations
Protection class IP 66



Asymmetric wide beam



Pole-top luminaires · single				
	LED	A	B	C
77 825	11.6 W	10 ¼	2 ⅙	20 ½
77 853	23.6 W	10 ¼	2 ⅙	20 ½
77 858	31.0 W	10 ¼	2 ⅙	20 ½

Pole-top luminaires · twin				
	LED	A	B	C
77 826	(2) 11.6 W	10 ¼	2 ⅙	37 ⅙
77 854	(2) 23.6 W	10 ¼	2 ⅙	37 ⅙
77 859	(2) 31.0 W	10 ¼	2 ⅙	37 ⅙



Davit arm luminaires				
	LED	A	B	C
77 827	16.0 W	10 ¼	2 ⅙	21 ⅞
77 855	38.0 W	10 ¼	2 ⅙	21 ⅞
77 897	50.6 W	10 ¼	2 ⅙	21 ⅞

Poles for above luminaires – see page 406 - 411.

