

Asymmetric wide beam

Area/roadway luminaires
with outrigger arm and asymmetric wide beam light distribution

A series of single and twin area/roadway luminaires with asymmetric wide beam light distribution and outrigger arm. This family of luminaires is designed specifically to illuminate streets, squares, access roads and pedestrian zones with maximum glare control and minimal spill light.


Die-cast aluminum
Clear safety glass with anti-reflective coating for increased transmission
Reflector made of pure anodized aluminum

LED color temperatures: 2700 K, 3000 K, 3500 K, 4000 K

BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at www.bega-us.com

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.

NRTL listed to North American standards · Suitable for wet locations
Protection class IP 66



Pole-top luminaires with outrigger · single				
	LED	A	B	C
77 950	31.0 W	10 ¼	2 ½	71 ¾

Pole-top luminaires with outrigger · twin				
	LED	A	B	C
77 953	(2) 31.0 W	10 ¼	2 ½	138 ½

Poles for above luminaires – see page 406 - 411.

