



Pole-top luminaires
with symmetric or asymmetric light distribution

A series of pole-top luminaires with symmetric or asymmetric wide beam light distribution. The symmetric light distribution is ideal for illuminating squares, plazas and other open areas while the asymmetric wide beam light distribution is ideal for illuminating streets and pathways.


Die-cast aluminum · Clear safety glass
Reflector made of pure anodized aluminum

LED color temperatures: 2700K, 3000K, 3500K, 4000K


BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at www.bega-us.com

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.


NRTL listed to North American standards · Suitable for wet locations
Protection class IP 65



Symmetric



Asymmetric wide beam



Pole-top luminaires · symmetric			
	LED	A	B
84 401	23.4 W	30 ⅞	14 ½
84 402	47.4 W	30 ⅞	14 ½

Pole-top luminaires · asymmetric wide beam			
	LED	A	B
84 403	23.6 W	30 ⅞	14 ½
84 404	51.6 W	30 ⅞	14 ½

Poles for above luminaires – see page 406 - 411.

