



Pole-top luminaires

with symmetric light distribution

A series of pole-top luminaires with symmetric light distribution and shallow height. The symmetric light distribution is ideal for illuminating squares, plazas and other open areas.


Die-cast aluminum · White acrylic diffuser

LED color temperatures: 2700K, 3000K, 3500K, 4000K

BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at www.bega-us.com

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.

NRTL listed to North American standards · Suitable for wet locations · Protection class IP 65



Symmetric



Pole-top luminaires			
	LED	A	B
88 100	16.8 W	24 1/4"	5 5/8"
88 164	25.2 W	24 1/4"	5 5/8"



Pole-top luminaires			
	LED	A	B
88 260	16.8 W	27 1/2"	12 5/8"
88 263	25.2 W	27 1/2"	12 5/8"

Poles for above luminaires – see page 406 - 411.

