

Symmetric



Asymmetric

**Pole-top luminaires**  
with indirect adjustable light distribution

A series of pole-top luminaires with adjustable indirect light distribution. Light from the luminaire is redirected by the top reflector creating soft and uniform light with superior glare suppression. Symmetric light distribution is produced when the top reflector is set in the horizontal position and an asymmetric light distribution when the reflector is swiveled from 0° to 30°.


Die-cast aluminum and stainless steel · Clear safety glass  
Reflector made of pure anodized aluminum

LED color temperatures: 2700 K, 3000 K, 3500 K, 4000 K

BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at [www.bega-us.com](http://www.bega-us.com)

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.

NRTL listed to North American standards · Suitable for wet locations · Protection class IP 65



Indirect			
	LED	A	B
<b>77 208</b>	35.7 W	31 ½	19 ¾
<b>77 210</b>	56.1 W	38 ¾	22 ½

Indirect · full cut-off			
	LED	A	B
<b>88 309</b>	56.1 W	38 ¾	22 ½

Poles for above luminaires – see page 406 - 411.

