



Symmetric



Asymmetric wide beam

Pole-top luminaires
symmetric or asymmetric wide beam light distribution

A series of pole top luminaires with symmetric or asymmetric wide beam light distribution. With an elegant form and extraordinary glare control, this luminaire provides visual interest both day and night. The very shallow profile of the optical housing is made possible by advancements in LED technology. The symmetric light distribution is ideal for illuminating squares, plazas and other open areas while the asymmetric wide beam light distribution is ideal for illuminating streets and pathways.

Die-cast aluminum · Clear acrylic diffuser with optical texture · Reflector made of pure anodized aluminum.

LED color temperatures: 2700 K, 3000 K, 3500 K, 4000 K

BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at www.bega-us.com

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.

NRTL listed to North American standards · Suitable for wet locations · Protection class IP 65



Pole-top luminaires · symmetric			
	LED	A	B
84 120	24.0 W	20 ⅞	22 ¼
84 147	47.2 W	29 ½	32 ⅝
84 305	101.0 W	29 ½	32 ⅝

Pole-top luminaires · asymmetric wide beam			
	LED	A	B
84 121	24.0 W	20 ⅞	22 ¼
84 148	47.2 W	29 ½	32 ⅝
84 306	101.0 W	29 ½	32 ⅝

Poles for above luminaires – see page 406 - 411.

