



**Pole-top luminaires**  
with unshielded, symmetric or asymmetric wide beam light distribution

A series of pole-top luminaires with symmetric or asymmetric wide beam light distribution with white or clear acrylic diffuser. Luminaires with translucent white acrylic diffuser are characterized by a symmetric and uniformly soft light distribution. Luminaires with clear acrylic diffuser are available optionally with symmetric or asymmetric light distribution.


Die-cast aluminum · Clear or white acrylic diffuser  
Reflector made of pure anodized aluminum

LED color temperatures: 2700K, 3000K, 3500K, 4000K

BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at [www.bega-us.com](http://www.bega-us.com)

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.

NRTL listed to North American standards · Suitable for wet locations  
Protection class IP 65




Unshielded · white diffuser			
	LED	A	B
<b>77 121</b>	16.0 W	15%	19 ¼
<b>77 122</b>	32.0 W	20 ⅙	26 ⅙


Symmetric · clear diffuser			
	LED	A	B
<b>77 124</b>	16.0 W	15%	19 ¼
<b>77 135</b>	32.0 W	20 ⅙	26 ⅙

Asymmetric wide beam · clear diffuser			
	LED	A	B
<b>77 150</b>	16.0 W	15%	19 ¼
<b>77 151</b>	32.0 W	20 ⅙	26 ⅙

Poles for above luminaires – see page 406 - 411.



Symmetric



Asymmetric wide beam

