



Wall luminaires
Light output on two sides

A family of wall luminaires with up and down light distribution. Sleek, precise edges of this luminaire housing are complemented by thick walled crystal glass accents. Whether as single features or aligned in rows, they illuminate and accentuate many situations in a room. Provided with electronic driver.

Crystal glass diffuser with white interior finish · Aluminum housing

Select the desired exterior finish by using appropriate code number as suffix

- White Code number **.1**
- Palladium Code number **.4**
- Velvet black Code number **.5**

Some luminaires on this page mount to a custom BEGA 19 538 recessed wiring box – see page 184. This wiring box is able to be shipped ahead of the luminaire. Refer to the luminaire installation instructions for details.

LED color temperatures: 2700K, 3000K, 3500K, 4000 K


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires – see page 186. Further LED technical data including luminous flux, CRI, service life, and dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at www.bega-us.com.

NRTL listed to North American Standards, interior use only
Refer to page 185 for more information


Select the desired exterior finish by using appropriate code number as suffix.



White
Code number **.1**



Palladium
Code number **.4**



Velvet black
Code number **.5**



| Wall luminaire | | | | | | |
|----------------|------------|--------|-----|-----|-----|---------------------|
| | | LED | A | B | C | Required wiring box |
| 50 063 | ADA | 7.6 W | 3 ½ | 4 ¾ | 4 | 19 538 |
| 50 064 | | 16.6 W | 4 ¾ | 6 | 5 ¼ | – |