



Wall luminaires
Light output on one side

Compact luminaires in two sizes with various light outputs. This family is well suited for installation on wide spacings to mark egress paths, or arranged in groups to create overlapping light distributions and increased light levels. The low wattage and long service life of the LED make these luminaires extremely cost-effective lighting solutions for both public and private projects.

Crystal glass diffuser with white interior finish · Die-cast aluminum housing

Select the desired exterior finish by using appropriate code number as suffix

- White Code number **.1**
- Stainless steel Code number **.2**


Some luminaires on this page mount to a custom BEGA 19 538 recessed wiring box – see page 184. This wiring box is able to be shipped ahead of the luminaire. Refer to the luminaire installation instructions for details.

LED color temperatures: 2700K, 3000K, 3500K, 4000K


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires – see page 186. Further LED technical data including luminous flux, CRI, service life, and dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at www.bega-us.com.

NRTL listed to North American Standards, interior use only
Refer to page 185 for more information

Select the desired exterior finish by using appropriate code number as suffix.



White
Code number **.1**



Stainless steel
Code number **.2**



Wall luminaire						
		LED	A	B	C	Required wiring box
78 047	ADA	2.1 W	3 ½	4	2 ⅛	19 538
78 052	ADA	4.2 W	6 ⅞	4	2 ⅛	–
50 071	ADA	6.1 W	6 ⅞	4	2 ⅛	–