



Wall luminaires
Unshielded

Hand-blown, three ply opal glass and precise metal accents in perfect harmony. This family of wall luminaires is a powerful lighting design tool for a variety of interior applications, arranged individually or in groups. A clearance of 50 % of the luminaire length - A - is required on one end of the luminaire for installation either vertically or horizontally. Provided with electronic driver.

Hand-blown, three-ply opal glass · Metal housing

Select the desired finish by using appropriate code number as suffix

- White Code number **.1**
- Stainless steel Code number **.2**
- Chrome Code number **.3**

All luminaires on this page mount to a custom BEGA 19 537 recessed wiring box – see page 184. This wiring box is able to be shipped ahead of the luminaire.

LED color temperatures: 2700K, 3000K, 3500K, 4000K

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires – see page 186. Further LED technical data including luminous flux, CRI, service life, and dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at www.bega-us.com.

NRTL listed to North American Standards, interior use only
Refer to page 185 for more information



Select the desired finish by using appropriate code number as suffix.



White
Code number **.1**



Stainless steel
Code number **.2**



Chrome
Code number **.3**



Wall luminaires					
	LED	A	B	C	Required wiring box
23 250	7.8 W	19 3/4	2 3/4	4 1/8	19 537
23 253	10.7 W	23 3/4	2 3/4	4 1/8	19 537
23 256	13.6 W	27 1/2	2 3/4	4 1/8	19 537
23 259	19.5 W	35 1/2	2 3/4	4 1/8	19 537