



## Ceiling and wall luminaires

A series of unshielded LED luminaires in three, seamless lengths for installation on ceilings or walls. LED technology and our own LED module production facilities enable us to pursue new avenues of luminaire design and to develop distinctive luminaires in special sizes. These unusually long lengths present new and creative options in many areas of interior design. The luminaires can be mounted in horizontal or vertical orientations. Provided with electronic driver.

Acrylic diffuser · Die-cast and extruded aluminum housing

Select the desired finish by using appropriate code number as suffix

• White Code number .1

• Matte aluminum Code number .2

All luminaires on this page mount to a custom BEGA 19 537 recessed wiring box – see page 184. This wiring box is able to be shipped ahead of the luminaire.

LED color temperatures: 2700 K, 3000 K, 3500 K, 4000 K

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires – see page 186. Further LED technical data including luminous flux, CRI, service life, and dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at www.bega-us.com.

NRTL listed to North American Standards, interior use only Refer to page 185 for more information

Select the desired finish by using appropriate code number as suffix.



White Code number .1



Matte aluminum Code number .2

. A . .C.

Ceiling and wall luminaire						
		LED	А	В	С	Required wiring box
50 142	ADA	35.2 W	41 3/8	2	3 1/8	19 537
50 143	ADA	50.4 W	61	2	3 1/8	19 537
50 144	ADA	70.4W	80 3/4	2	3 1/8	19 537