



Ceiling and wall luminaires

A family of luminaires with high-quality, hand-blown glass, featuring a precise and distinctly contoured glass edge. Available in three sizes, all with a shallow projection from the finished surface. These luminaires balance efficacy and elegance for use in a wide variety of interior space types.

Luminaires in this series are also available with an impact resistant acrylic diffuser for special applications, add **P** as suffix. Provided with electronic driver.

Hand-blown, three-ply opal glass, satin matte finish or impact resistant acrylic diffuser Aluminum housing, white finish

LED color temperatures: 2700 K, 3000 K, 3500 K, 4000 K

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires – see page 186. Further LED technical data including luminous flux, CRI, service life, and dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at www.bega-us.com.

NRTL listed to North American Standards, interior use only Refer to page 185 for more information



| Ceiling and wall luminaire | | | | | |
|----------------------------|-----|--------|-------|-------|--------------------|
| | | LED | Α | В | С |
| 34 287 | ADA | 16.4W | 131/4 | 3 3/8 | 10 1/2 |
| 34 288 | ADA | 25.9 W | 153/8 | 3 1/8 | 11 ⁷ /8 |
| 23 297 | ADA | 37.8W | 181/2 | 3 1/8 | 14 1/4 |