



## Ceiling and wall luminaires

Expertly hand crafted glass combined with cost effective and durable technology. Available in multiple size and lumen output combinations, these ceiling and wall luminaires offer a broad range of lighting design opportunities. Perfect proportions and impressive glass help these luminaires make a lasting impression.

Luminaires in this series are also available with an impact resistant acrylic diffuser for special applications, add **P** as suffix. Provided with electronic driver.

Hand-blown opal glass with screw neck or impact resistant acrylic diffuser with screw neck · Metal mounting plate, white finish

LED color temperatures: 2700 K, 3000 K, 3500 K, 4000 K

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires – see page 186. Further LED technical data including luminous flux, CRI, service life, and dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at www.bega-us.com.

NRTL listed to North American Standards, interior use only Refer to page 185 for more information



Ceiling a	and wall	luminaire			
	LED		Α	В	С
23 296	ADA	8.1 W	133/4	3 1/4	9 1/2
23 410	ADA	11.9W	133/4	3 1/4	9 1/2
23 414	ADA	17.4 W	16 1/2	4	11
12 163	ADA	25.2 W	16 1/2	3 7/8	11
12 164		37.8W	20 1/8	4 5/8	14