



Ceiling and wall luminaires

These shallow designs are only possible with the integration of compact, reliable and cost-effective LED sources. This family of luminaires is a unique combination of the age-old glassmaker's art with the latest lighting technology. Available in three housing finishes and distinct glass diffusers allowing for the perfect coordination with other architectural details.  
Provided with electronic driver.

Crystal glass diffuser with white interior finish or hand-blown, three-ply opal glass, satin matte finish · Aluminum housing

Select the desired finish by using appropriate code number as suffix

- White Code number **.1**
- Stainless steel Code number **.2**
- Polished aluminum Code number **.3**

LED color temperatures: 2700 K, 3000 K, 3500 K, 4000 K

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires – see page 186. Further LED technical data including luminous flux, CRI, service life, and dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at [www.bega-us.com](http://www.bega-us.com).

NRTL listed to North American Standards, interior use only  
Refer to page 185 for more information



Select the desired finish by using appropriate code number as suffix.




White  
Code number **.1**



Stainless steel  
Code number **.2**



Polished aluminum  
Code number **.3**



Ceiling and wall luminaire · Crystal glass					
		LED		A	B
<b>12 127</b>	<b>ADA</b>	14.2W		10 3⁄8	2 5⁄8
<b>12 128</b>	<b>ADA</b>	19.6W		12	2 5⁄8

Ceiling and wal luminaire I · Opal glass					
		LED		A	B
<b>12 130</b>	<b>ADA</b>	14.2W		10 3⁄8	2 5⁄8
<b>12 131</b>	<b>ADA</b>	19.6W		12	2 5⁄8