

Ceiling and wall luminaires

A family of luminaires with high-quality, hand-blown glass, featuring a precise and distinctly contoured glass edge. The light is shielded on the sides by a metal housing which creates a striking contrast between the glowing glass and housing. At the same time, indirect light between the wall or ceiling surface and metal housing make the luminaires appear as if they are floating. Available in three sizes and two exterior finishes.

Luminaires in this series are also available with an impact resistant acrylic diffuser for special applications, add **P** as suffix. Provided with electronic driver.

Hand-blown, three-ply opal glass, satin matte finish or impact resistant acrylic diffuser
Aluminum housing

- Select the desired finish by using appropriate code number as suffix
- White Code number **.1**
 - Silver Code number **.2**


LED color temperatures: 2700 K, 3000 K, 3500 K, 4000 K

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires – see page 186. Further LED technical data including luminous flux, CRI, service life, and dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at www.bega-us.com.


NRTL listed to North American Standards, interior use only
Refer to page 185 for more information




Select the desired finish by using appropriate code number as suffix.



White
Code number **.1**



Silver
Code number **.2**



Ceiling and wall luminaire					
		LED	A	B	C
34 278	ADA	16.4 W	14 1⁄8	3 3⁄8	10 1⁄2
34 279	ADA	25.9 W	16 1⁄2	3 3⁄8	11 1⁄4
12 165	ADA	37.8 W	19 3⁄4	3 3⁄8	14 1⁄4