



Semi-recessed ceiling luminaire
Unshielded
Tunable white

A family of hand-blown, three-ply opal glass luminaires with a distinctive form, available with tunable white technology. These unshielded, semi-recessed luminaires with wide beam distribution are characterized by very shallow heights and compact dimensions. A diffuse lens with concave interior creates a smooth light gradient across the satin matte glass, resulting in a unique combination of the age-old glassmaker's art paired with the latest lighting technology. Provided with electronic driver in ceiling box or optional ceiling pan. Refer to the luminaire installation instructions for required minimum ceiling clearance.

Hand-blown, three-ply opal glass, satin matte finish · Aluminum housing

LED color temperatures: 2700 K, 3000 K, 3500 K, 4000 K

Tunable white color temperature range is adjustable from 2700 K to 6500 K via DALI control protocol

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires – see page 186. Further LED technical data including luminous flux, CRI, service life, and dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at www.bega-us.com.

NRTL listed to North American Standards, interior use only
Refer to page 185 for more information



Ceiling luminaire				
	LED	A	B	C
34 560	7.5 W	5 3/8	1 3/4	1 3/4
34 562	9.6 W	6 1/4	1 3/4	2
34 859	13.5 W	7	1 3/4	2 3/8
34 864	17.7 W	8 7/8	1 3/4	2 3/4
50 177	37.5 W	10 3/8	2 3/8	3

Ceiling luminaire · Tunable white				
	LED	A	B	C
50 270	14.8 W	7	1 3/4	2 3/8
50 271	16.5 W	8 7/8	1 3/4	2 3/4
50 195	21.4 W	10 3/8	2 3/8	3



Ceiling luminaires · page 76



Pendant luminaires · page 154