

Recessed ceiling and wall luminaires
Tunable white

Luminaires with high light output, characterized by their low profile and shallow recessed depth, available with tunable white technology. A family of luminaires designed to illuminate rooms, stairways, or hallways while creating an intriguing contrast between the luminaire and the mounting surface. The hand-blown, three-ply opal glass distributes diffuse light uniformly throughout a space. These luminaires are equipped with a mounting system for easy, economic, and convenient installation. Provided with electronic driver in ceiling or wall box. Refer to the luminaire installation instructions for required minimum recessed clearance.

Hand-blown, three-ply opal glass, satin matte finish with screw neck
Aluminum housing

Select the desired trim ring finish by using appropriate code number as suffix

- White Code number **.1**
- Stainless steel Code number **.2**

LED color temperatures: 2700 K, 3000 K, 3500 K, 4000 K

Tunable white color temperature range is adjustable from 2700 K to 6500 K via DALI control protocol


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires – see page 186. Further LED technical data including luminous flux, CRI, service life, and dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at www.bega-us.com.

NRTL listed to North American Standards, interior use only
Refer to page 185 for more information



Ceiling and wall luminaire				
		LED	A	B
50 523	ADA	8.4 W	7 1⁄8	2 3⁄8
50 524	ADA	17.8 W	10	2 3⁄8
50 525	ADA	28.1 W	13 3⁄8	2 3⁄8
50 526	ADA	43.7 W	16 7⁄8	2 3⁄8

Ceiling and wall luminaire · Tunable white				
		LED	A	B
50 289	ADA	8.5 W	7 1⁄8	2 3⁄8
50 290	ADA	18.1 W	10	2 3⁄8
50 291	ADA	28.1 W	13 3⁄8	2 3⁄8
50 292	ADA	33.0 W	16 7⁄8	2 3⁄8



Select the desired trim ring finish by using appropriate code number as suffix.



White
Code number **.1**



Stainless steel
Code number **.2**