



For recessed ceiling luminaires, see page 38.



For pendant luminaires, see page 154.

Select the desired exterior finish by using appropriate code number as suffix.



White
Code number .1



Stainless steel
Code number .2



Polished aluminum
Code number .3



Ceiling luminaires

Unshielded

LED ceiling luminaires available in four sizes and three exterior finishes. The unique hand-blown, three-ply opal glass with a concave interior surface provides soft, uniform light. These luminaires are a perfect combination of the age-old art of glass making with the latest lighting technology. Provided with electronic driver.

Hand-blown, three-ply opal glass, satin matte finish with screw neck
Aluminum housing

Select the desired exterior finish by using appropriate code number as suffix

- White Code number .1
- Stainless steel Code number .2
- Polished aluminum Code number .3

Some luminaires on this page mount to a custom BEGA 19 538 recessed wiring box – see page 184. This wiring box is able to be shipped ahead of the luminaire. Refer to the luminaire installation instructions for details.

LED color temperatures: 2700K, 3000K, 3500K, 4000K

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires – see page 186. Further LED technical data including luminous flux, CRI, service life, and dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at www.bega-us.com.

NRTL listed to North American Standards, interior use only
Refer to page 185 for more information



Ceiling luminaire					
	LED	A	B	Required wiring box	
23 846	3.0W	4	3 7/8	19 538	
23 966	7.5W	4 7/8	3 7/8	-	
23 967	9.6W	5 5/8	4 3/8	-	
34 021	13.5W	7 1/2	5 1/8	-	